

WISEASY T1

EMV Android Tablet



Diverse Payments



Full Screen Touch Tablet
with Magnetic Stand



Commercial Security
Operating System



IC/Magnetic Card
Reading & Writing



Multiple Interfaces
for Peripheral Devices



External Printer



Biometric Features Module
(Optional)



- Android 10.1 security operating system, Qualcomm Octa-core processor, running speed is greatly improved.
- Fully compatible with encrypted magnetic stripe card, financial IC card, NFC, BLE, sound wave and other payment technology.
- Full screen tablet touch experience, magnetic suction supports matching use, supports desktop + handheld multi-scene applications.
- Financial level technical security and protection threshold, anti-disassembly, anti-attack, anti-spy protection hardware and structural physical security design.
- Highly integrated industrial design, reserved with multiple USB interfaces, network ports and other interfaces on the base, can be connected to keyboard, printer and other peripherals.



Magnetic Dock Stand 1



Magnetic Dock Stand 2



Cashier Box1



Printer M58

Technical Specifications

 Operating System Android 10.1, WiseOS	 CPU Qualcomm Octa-Core 1.8GHz	 Memory 2GB+16GB Standard	 Display 11.6 inches, resolution: 1920*1080 10 points touch screen	 Camera Front camera: 5Mega Rear camera: 8Mega, Supports auto focus & flashlight
 Network 2G/3G/4G	 WIFI 2.4G/5G, 802.11 a/b/g/n/ac	 Bluetooth Bluetooth4.2, BLE	 GPS GPS/AGPS/GLONASS/ Beidou	 NFC 13.56MHz, Support EMV2.6b standard ISO/IEC 14443, ISO18092, Type A&B, Felica, Mifare
 IC Card Reader 1. ISO7816 2. PBOC3.0 L1/L2	 Magnetic Card Reader ISO7810/7811, Support three-track two-way manual swinging	 Printer Bluetooth and USB Printer	 USB Port Type C USB2.0, High Speed, OTG.	 Card Slot 1 * Micro SIM + 1* Micro PSAM or 2 * SIM, Supports DSDS (SAM slot) & the SIM card
 Audio Single speaker, 1.2w	 Battery 3.7v/6450mAh, supports fast charging	 Adapter Input: AC 100-240V, 50/60Hz Output: 9V/2A	 Weight T1: 1006g Bracket 1: 1200g Bracket 2: 1075g	 Dimensions T1: 287.3*180.9*18.7 mm Bracket 1: 239.5*219.5*195.6 mm Bracket 1: 239.5*219.5*188.8 mm
 Dock Stand Option 1: Fingerprint: Optional RJ45: Supports RJ45, WLAN and Ethernet USB: 3*Type A USB ports Wire Charger: DC interface, 9V/2A Standing Charger: Magnetic suction connection charging	Option 2: USB: 1*Type A USB ports Wire Charger: DC interface, 9V/2A Standing Charger: Magnetic suction connection charging		 Temperature Storage temperature: -35°C to 70°C Operating temperature: -10°C to 55°C Humidity: ≤95%	

Certifications

**EMV Contact L1 / EMV Contactless L1 2.6b / EMV Contact L2 / VISA / MASTERCARD / AMEX / DISCOVER / PCI / TQM / State secret certification
GSMA / EU CE / India BIS / Mexico NOM / RoHS / CB**