

WISEASY P5

EMV Android POS



Quad Cortex-A53
at 2.0GHz



2GB LPDDR4 + 32GB eMMC



Android 11



Professional
scanning module



5.5-inch full screen
with thin bezel


























High-speed
thermal printer

- Equipped with Quad-core processor and Android 11 Operating System for better performance and lower power consumption
- 5.5-inch full screen with thin bezel
- More compact paper cabin for smaller size
- Professional thermal printer for speed up to 100mm/s
- Finely crafted curves, comfortable one-hand operation experience



Charging Cradle (Optional)

Technical Specifications

 Model Name P5	 Operating System WiseOS 3.0 Based on Android 11	 CPU Quad Cortex-A53 at 2.0GHz	 Memory 2GB LPDDR4 + 32GB eMMC	 Security Processor Max 32555
 Display 5.5 inch IPS Screen, 1280x720 HD Capacitive Multi-Point Touch Panel	 Network 2G/3G/4G	 WIFI 2.4G/5G, IEEE802.11 a/b/g/n/ac	 Bluetooth Bluetooth5.0, BLE	 GPS GPS/A-GPS, Glonass, Beidou
 Camera Front Camera: 2M FF(optional) Rear Camera: 5M AF (2D Scan Engine optional)	 Fingerprint FAP10, FBI/STQC (Optional)	 Audio Speaker: 1W Mic (optional)	 NFC 13.56MHz, ISO/IEC14443 TypeA&B, Mifare S50/S70, Felica	 Card Readers MSR: ISO7810-7813 3 tracks IC Card: ISO7816
 Card Slot 2*Micro SIM slot + 2*PSAM Slot +1*T-Flash slot, up to 128GB * Fiscal Module optional	 Button Power Button / Scan Button	 Battery Removable Lithium polymer battery, 7.4V/2620mAh	 Peripheral Ports Type C USB2.0 OTG 5*Pogo Pin	 Weight 443g
 Size (L*W*H) 209.09*78.59*19mm	 Printer 2"High Speed Thermal Printer Roll Size: 58*40mm Print Speed: 100mm/s Laboratory tested	 Adapter Input: AC 100-240V, 50/60Hz Output: 5V/2A	 Environment Storage temperature: -20°C to 60°C Operating temperature: -10°C to 55°C Humidity: ≤95%	 Accessories Optional: Charging Cradle, Multi-port Charging Cradle

Certifications

EMV Contact L1 / EMV Contactless L1 / EMV Contact L2 / VISA / MASTERCARD / AMEX / DISCOVER / PCI 6.1 / TQM / UPI / JCB MIR / RuPay / eftpos / BIS / WPC / CEC / DOE / CA65 / Pure / CE / FCC / CB / IC / ROHS / WEEE / KC / OFCA / Google GMS